

The Elettra Storage Ring and Top-Up Operation

Emanuel Karantzoulis


14th ESLS RF Workshop

ELETTRA / Trieste, Italy / 2010 September 29 30




Past and Present Configurations

1994- 2007



From 2008



5000 hours /year to the users



14th ESLS RF Workshop

ELETTRA / Trieste, Italy / 2010 September 29 30





2010: Operations transition year


Decay mode, 2 GeV (340mA) and 2.4 GeV (140) – FEL at 1 GeV.

Top-up at 2 GeV (300mA) and 2.4 GeV (140) – FEL upgrades to 2 GeV to be users compatible; for the moment 1.8 GeV 130 nm.

Fill: Any, mainly multibunch and on request hybrid. SB exists but not requested except for FEL.



Machine Parameters



Beam energy [GeV]		2	2.4
Storage ring circumference [m]	259.2		
Beam height in experimental area [m]	1.3		
Number of achromats	12		
Length of Insertion Device (ID) straight sections [m]	6(4.8 utilizzabile per ID's)		
Number of straight sections of use for ID's	11		
Number of bending magnet source points	12		
Beam revolution frequency [MHz]	1.157		
Number of circulating electron bunches	1 - 432		
Time between bunches [ns]	864 - 2		
Tunes: horizontal/vertical	14.3/8.2		
Natural emittance [nm-rad]	7	9.7	
Energy lost per turn without ID's [keV]	255.7	533	
Maximum energy lost per turn with ID's [keV] (all)	315	618.5	
Critical energy [keV]	3.2	5.5	
Bending magnet field [T]	1.2	1.45	
Geometrical emittance coupling %	≤ 1%		
Spurious dispersion (at the centre of ID's): horizontal (rms max/min) [cm]	6/2.		
Spurious dispersion (at the centre of ID's): vertical (rms max/min) [cm]	2/0.5		
Operation mode	multibunch		
One refill per day (09:30) of duration (incl. ramping etc.) [min]	30		
Injection energy [GeV]	0.75 / 0.9 / 1		
Injected current [mA]		320	140
Machine dominated by the Touschek effect			
Energy spread (rms) %		0.08	0.12
Lifetime [hours]		8.5	26
Bunch length (1 σ) [mm] &		5.4	7
Beam dimensions (1 σ) &			
ID source point - horizontal/vertical [μ m]		241/15	283/16
Bending magnet source point - horizontal/vertical [μ m]		139/28	197/30
Beam divergence (1 σ) &			
ID source point - horizontal/vertical [μ rad]		29/6.	35/8.
Bending magnet source point - horizontal/vertical [μ rad]		263/9	370/13
&: The values shown (taking into account the energy spread) are averages, obtained from a consideration of different angle and position values of the spurious dispersion and can vary by $\pm 10\%$			



Elettra's new injector

- 2005 project funded
- 2007 autumn connection with SR
- 2008 Finished on time (3 March 2008 for user shifts already programmed since 2007) and within budget

- Difficulties with the booster main PSs
- Stability
- Reproducibility



110 MeV pre-injector

- Linac made of a thermionic gun, cathode Th306 Thales, a 500 MHz pre bunching cavity, an S-band 3 GHz bunching structure and two LIL (CERN) 5 m accelerating sections of about 50 MeV each providing thus ≥ 10 MeV / m .
- The sections are powered by a 3 GHz 45 MW pulsed Thales 2132A S-band klystron using a MDK modulator

Performs quite well, still margin for improvement especially on the klystron discharges; many are false

- water/ambient temp stability is vital
- Spare gun and modulator constructed (redundancy)



Booster

Magnet lattice	FODO with missing magnets
Maximum energy	2.5 GeV
Injection energy	100 MeV
RF frequency	499.654 MHz
Circumference	118.8 m
Revolution period	396 ns
Harmonic number	198
Equilibrium emittance (2.5 GeV)	
Normal Emittance Optic	226 nm.rad
Low Emittance Optic	166 nm.rad
r.m.s. energy spread (2.5 GeV)	$7.18 \cdot 10^{-4}$
Energy loss per turn (2.5 GeV)	388 keV
Damping times (h,v,l) (2.5 GeV)	5.1, 5.1, 2.6 ms
Betatron tunes Q_x, Q_y	5.39, 3.42
	6.8, 2.85
Natural chromaticities ξ_x, ξ_y	-6.6, -4.7
	-11.1, -5.2
Momentum compaction factor	0.0443
	0.0308
Maximum β_x, β_y, D_x	10.8, 13.8, 1.621 m
	15.0, 17.2, 1.683 m
Peak effective RF voltage	0.84 MV ($\tau_q \sim 1$ s)
<i>(available 1.1MV)</i>	0.73 MV ($\tau_q \sim 1$ s)

	Nominal	Low Emitt.	
Beam energy	2.5	2.5	GeV
Beam current	5	5	mA
Energy loss	388	388	keV
Harmonic number	198	198	
Revolution freq.	2.524	2.524	MHz
RF frequency	499.654	499.654	MHz
Mom. compaction	0.0433	0.0308	
Quantum lifetime	1	1	sec.
Overvoltage factor	2.16	1.58	
Total RF voltage	840	730	kV
Energy acceptance	3.07E-3	3.07E-3	
Cavity power	25.20	19.03	kW
Beam power	1.94	1.94	kW
Total RF power	27.14	20.97	kW



14th ESLS RF Workshop


ELETTRA / Trieste, Italy / 2010 September 29 30




Booster / 2

RF plant from Elettra (RF9) 500 MHz 60 kW (TV klystron) and a 5-cell PETRA type cavity. Power transmission via coaxial line. The system performs well.





Many problems mainly due to big PSs (also their controls); hard work of about 1 year main problems fixed



- Acceptable operations established. Booster operates at full cycle (2.5 GeV) and up to 3 Hz
- Full energy injection to Elettra at any energy up to 2.4 GeV and any filling (multibunch , single bunch , few bunch) up to 2.4 Hz rep. rate with efficiencies up to 100%




Booster PS faults




Elettra Availability

Availability on scheduled user beam time



2010 Elettra uptime




14th ESLS RF Workshop

ELETTRA / Trieste, Italy / 2010 September 29 30




Systems Failures in % of User Downtime 2010





14th ESLS RF Workshop

ELETTRA / Trieste, Italy / 2010 September 29 30





Includes air conditioning too



14th ESLS RF Workshop

ELETTRA / Trieste, Italy / 2010 September 29 30



Top Up

Implementation to the machine achieved in 1 year (2009)

Radioprotection measurements finished as scheduled by end of March 2010. However due to 2 low gap chamber installation during the April shutdown some more controls were required in May.

On May 10, top-up operations for users was implemented at 2.0 GeV.

On May 24, top-up operations for users was implemented at 2.4 GeV

Gating is provided via internet, some lines have also additional interface boards provided by the top-up team.

The screenshot shows the ELETTRA website interface. At the top right is the 'elettra' logo. A vertical navigation menu on the left includes: back to homepage, ELETTRA, organisation, user information, access request, machine status & operations (highlighted), operating schedule, beamtime allocation calendar, parameters, operations and development, science & publications, projects, visitor guide, and intranet. Below the menu are 'Quick Links' for PhD fellowships, Occupational Health & Safety, Radiation Protection, Industrial Liaison Office, employment opportunities, welcome office, international students & researchers, procurement, avvisi, and broad area announcements. At the bottom left of the menu is 'Internal Services'. The main content area is titled 'Machine Status' and displays: Current: 299.40 mA, Lifetime: 21 h, Energy: 2.000 GeV, and Operation Mode: Multi bunch. Below this is 'Machine information' with details: Machine status: Users dedicated; Next Users dedicated injection: 21 May at TOP-UP mode; Machine Operator: Pasqualetto M. A red dashed box contains the text: 'Topup status for beamlines available at link: 140.105.3.130/blcs/FRONTEND/MACHINE/TCPS_1 TOPUP Status legenda: ON - topup refill enabled, WARMUP - preparing for injection, RUNNING - injection running.' Two charts are shown: 'Current (last 12 hours)' and 'Current (last 48 hours)'. Both charts show a constant current level of approximately 300 mA. The 12-hour chart shows a red bar, and the 48-hour chart shows an orange bar. The 48-hour chart x-axis spans from Thu 22:00 to Sat 08:00. Below the charts is the text: 'Charts at: Sat, 22 May 2010 11:57:02 +0200'.

[View](#) the operating status of the beamline.


[View](#) the Photon Beam.




14th ESLS RF Workshop



Refill / Top-up controller




Next, fast dcct already installed will allow bunch to bunch fill




14th ESLS RF Workshop



Systems stability during top-up



> 90%
homogeneity
within 1 mA in 56
hours




14th ESLS RF Workshop

ELETTRA / Trieste, Italy / 2010 September 29 30




e-bpm system – ambient temperature effects




No top up, current decay from 330 to 260 mA – slow drift of horizontal beam position in the middle of ID9 of about 7 μm in 5 hours

Oscillations are due to the Libera e-bpm electronics being affected by ambient temperature oscillations in the Service Area (± 2 deg).




Top up at 300 mA – no drift, peak to peak 1.5 μm




Long term stability

from 16/9/2010 00:00 to 20/9/2010 06:00


for 102 hours



4 μm



1.5 μm




SLS RF Workshop

te, Italy / 2010 September 29 30



Beam
current



14th ESLS RF Workshop

ELETTRA / Trieste, Italy / 2010 September 29 30



Actual working projects

- Installed 2 low gap (9mm) chambers
- Air cooling of hot points to increase the intensity (but users very reluctant)
- Ambient temp stabilization
- Realignment
- BBA
- 8th corrector
- Photon bpm



Present Conclusions

- *Top up is now the regular mode of operations*
- *A big effort towards reproducibility and stabilization is under way*

Acknowledgements to :

A. Carniel, S. Krecic, M. Vento and the operators

G. Gaio, F. Giacuzzo, C. Scafuri , L. Zambon and the controls

K. Casarin, E. Quai, G. Tromba, A. Vascotto and the radioprotection

O. Ferrando and S. Ferry for simulations and algorithms

...and certainly all members of the ODAC project



Looking to the future (next 3 years)

- Installation of skew elements and other improvements
BUT most important:
- Should we continue with IOTs or move towards solid state? (assume that returning to klystrons is out of question?)

I hope by the end of this workshop we can get some answer

I wish all of you a very successful workshop

